

FIG. 1

2/23




FIG. 2

3/23




FIG. 3

4/23




FIG. 4

5/23




FIG. 5




FIG. 6

7/23




FIG. 7

8/23




FIG. 8

9/23




FIG. 9

10/23

10A	10B
-----	-----

FIG. 10




FIG. 10A

11/23





FIG. 10B


12/23

FIG. 11



12A 12B

FIG. 12






FIG. 12B




FIG. 13

16/23




FIG. 14

17/23




FIG. 15A

18/23




FIG. 15B

19/23




FIG. 16

Diagram 1700 illustrates a table structure. The table has six rows, each with a field name and a reference numeral: 1710 for 'NodeID', 1720 for 'LinkCost', 1730 for 'QoS3Capacity', 1740 for 'QoS4Capacity', 1750 for 'HelloInterval', and 1760 for 'TimeoutInterval'.

NodeID	1710
LinkCost	1720
QoS3Capacity	1730
QoS4Capacity	1740
HelloInterval	1750
TimeoutInterval	1760

FIG. 17




FIG. 18

1900

Zero-byte	1905	LSA count	1910
Node ID		1930(1)	
Node ID		1930(2)	
Node ID		1930(N-1)	
Node ID		1930(N)	

FIG. 19

VPID		<u>2010</u>	Path 2050
Checksum		<u>2020</u>	
PathLength	<u>2030</u>	HopCount	
Hop		<u>2060(1)</u>	
Hop		<u>2060(2)</u>	
Hop		<u>2060(N)</u>	

FIG. 20

23/23

↙ 2100

VPID		<u>2110</u>
Checksum		<u>2121</u>
PathLength	<u>2130</u>	HopCount <u>2140</u>
Hop		<u>2160(1)</u>
Hop		<u>2160(2)</u>
Hop		<u>2160(N)</u>

Path
┌ 2150

FIG. 21